ZINGACERAM PU - COMP. A

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 13/02/2015 Revision date: Supersedes: 27/09/2013 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : ZINGACERAM PU - COMP. A

Type of product : Paint

Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Industrial
For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

ZINGAMETALL B.V.B.A.
Rozenstraat 4, Industriepark 9810 Eke België
Tel. : +32 (0)9 385 68 81
Fax. : +32 (0)9 385 58 69
E-mail : zingametall@zinga.be

1.4. Emergency telephone number

Emergency number : +32(0)70/245.245 (B)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Skin Sens. 1	H317

Full text of H-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02 GHS07

Signal word (CLP) : Danger

Hazardous ingredients : Polyacrylaat

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P261 - Avoid breathing vapours, spray, mist, gas
P264 - Wash hands, forearms and face thoroughly after handling

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	13,01026 - 31,10296	R10 Xn; R20/21 Xi; R38
Polyacrylaat	(CAS No) 37237-99-3	15 - 30	R43
ethylbenzene	(CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4	2,000072 - 4,0009	F; R11 Xn; R20 Xn; R65 Xn; R48/20

Name	Product identifier	Specific concentration limits
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	(C >= 12,5) Xn;R20/21

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
xylene	(CAS No) 1330-20-7 (EC no) 215-535-7 (EC index no) 601-022-00-9	13,01026 - 31,10296	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315
Polyacrylaat	(CAS No) 37237-99-3	15 - 30	Skin Sens. 1, H317
ethylbenzene	(CAS No) 100-41-4 (EC no) 202-849-4 (EC index no) 601-023-00-4	2,000072 - 4,0009	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:dust,mist), H332

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Allow victim to breathe fresh air. Allow the victim to rest.

First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment (see ... on this label). If skin irritation or rash occurs:

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause an allergic skin reaction.

Symptoms/injuries after skin contact : Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Wash ... thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/… equipment.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m³)	221 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	442 mg/m³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Belgium	Local name	Xylène, isomères mixtes, purs
Belgium	Limit value (mg/m³)	221 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	442 mg/m³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
ethylbenzene (100-41-4)		
EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m³)	442 mg/m³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m³)	884 mg/m³
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin

ethylbenzene (100-41-4)		
Belgium	Local name	Ethylbenzène
Belgium	Limit value (mg/m³)	442 mg/m³
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m³)	551 mg/m³
Belgium	Short time value (ppm)	125 ppm
Belgium	Remark (BE)	D

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves

Eye protection : Chemical goggles or safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : Wear appropriate mask

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Different colours.

Odour : characteristic.

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : No data available

Flash point : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapour,Highly flammable liquid and vapour

Vapour pressure : No data available

Relative vapour density at 20 °C : No data available

Relative density : No data available

Density : 1,19 - 1,38 kg/l

Solubility : Not soluble in water, so only minimally biodegradable.

Log Pow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidising properties : No data available

Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	:	Not classified
Skin corrosion/irritation	:	Causes skin irritation.
Serious eye damage/irritation	:	Not classified Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	:	May cause an allergic skin reaction.
Germ cell mutagenicity	:	Not classified Based on available data, the classification criteria are not met
Carcinogenicity	:	Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	:	Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	:	Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (repeated exposure)	:	Not classified Based on available data, the classification criteria are not met
Aspiration hazard	:	Not classified Based on available data, the classification criteria are not met
Potential adverse human health effects and symptoms	:	Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

ZINGACERAM PU - COMP. A	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

ZINGACERAM PU - COMP. A	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Additional information : Avoid release to the environment

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	:	Disposal must be done according to official regulations.
Waste disposal recommendations	:	Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Additional information	:	Clean up even minor leaks or spills if possible without unecessary risk. Flammable vapours may accumulate in the container. Industrial waste. Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials	:	Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
1263	1263	1263	1263	1263
14.2. UN proper shipping name				
PAINT	PAINT	Paint	PAINT	PAINT
Transport document description				
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III			
14.3. Transport hazard class(es)				
3	3	3	3	3
				
14.4. Packing group				
III	III	I	III	III
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No

14.6. Special precautions for user

14.6.1. Overland transport

Classification code (ADR) : F1
Special provisions (ADR) : 163, 640E, 650
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E

14.6.2. Transport by sea

Special provisions (IMDG) : 163, 223, 955
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A

Properties and observations (IMDG)	:	Miscibility with water depends upon the composition.

14.6.3. Air transport

PCA Excepted quantities (IATA)	:	E3
PCA Limited quantities (IATA)	:	Forbidden
PCA limited quantity max net quantity (IATA)	:	Forbidden
PCA packing instructions (IATA)	:	351
PCA max net quantity (IATA)	:	1L
CAO packing instructions (IATA)	:	361
CAO max net quantity (IATA)	:	30L
Special provisions (IATA)	:	A3, A72
ERG code (IATA)	:	3L

14.6.4. Inland waterway transport

Classification code (ADN)	:	F1
Special provisions (ADN)	:	163, 64E, 65
Limited quantities (ADN)	:	5 L
Excepted quantities (ADN)	:	E1
Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01
Number of blue cones/lights (ADN)	:	0
Not subject to ADN	:	No

14.6.5. Rail transport

Classification code (RID)	:	F1
Special provisions (RID)	:	163, 640E, 650
Limited quantities (RID)	:	5L
Excepted quantities (RID)	:	E1
Packing instructions (RID)	:	P001, IBC03, LP01, R001
Special packing provisions (RID)	:	PP1
Mixed packing provisions (RID)	:	MP19
Portable tank and bulk container instructions (RID)	:	T2
Portable tank and bulk container special provisions (RID)	:	TP1, TP29
Tank codes for RID tanks (RID)	:	LGBF
Transport category (RID)	:	3
Special provisions for carriage – Packages (RID)	:	W12
Colis express (express parcels) (RID)	:	CE4
Hazard identification number (RID)	:	30
Carriage prohibited (RID)	:	No

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Polyacrylaat
3.b. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Polyacrylaat

40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	xylene

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
R10	Flammable
R11	Highly flammable
R20	Harmful by inhalation
R20/21	Harmful by inhalation and in contact with skin
R38	Irritating to skin
R43	May cause sensitisation by skin contact
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation
R65	Harmful: may cause lung damage if swallowed
F	Highly flammable
Xi	Irritant
Xn	Harmful

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product